

# CAMSO MPT 774



BACKHOE  
LOADERS



COMPACT  
WHEEL LOADERS



## HEAVY-DUTY COMBINATION OF DURABILTY AND PUNCTURE RESISTANCE

Tough and durable pneumatic tire solution for backhoe and compact wheel loaders. Best choice for rocky and severe-duty applications.

[camsos.co](http://camsos.co)

## PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



# CAMSO MPT 774



**DEEP TREAD PATTERN WITH HIGH LUG-TO-VOID RATIO**

- Provides excellent tire life and tread impact resistance

**EXTRA THICK VOID GUARD**

- Maximizes tread impact protection to reduce risk of punctures

**NON-DIRECTIONAL, STEPPED TREAD DESIGN WITH INNOVATIVE OPEN SHOULDERS**

- Enhances self-cleaning and versatility

**IMPACT GUARD WITH ENHANCED RIM PROTECTION**

- Protects sidewalls and rim flanges, reducing impact damage and flat tires

TIRE SIZE	PR	RIM SIZE	ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	INFLATION PRESSURE [bar] [PSI]	LOAD CAPACITY [kg] [lb]					
		ALTERNATIVE SIZE	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32 <sup>nd</sup> ]	S.L.R. [mm] [in]	R.C. [mm] [in]						Static	5 km/h 3 mph	10 km/h 6 mph	25 km/h 16 mph	40 km/h 25 mph	50 km/h 31 mph
320/80-18 IND	18	12.5/80-18 320/80R18 12.5/80R18	966	337	40	452	2875	139	A8	R-4	INDUSTRIAL TRACTOR	4.00	5590	4060*	3645*	2695	2430	2210
			38	13.3	50	17.8	113.2					58	13325	8950*	8035**	5940	5355	4870
320/80-18 IND	18	12.5/80-18 320/80R18 12.5/80R18	966	337	40	452	2875	139	A8	R-4	INDUSTRIAL TRACTOR	4.00	5590	3525*	3040**	2575	2430	2210
			38	13.3	50	17.8	113.2					58	13325	7770*	6700*	5675	5355	4870

\* Cyclic: One way distance up to 150 m (500 feet)

\*\* Cyclic: One way distance up to 600 m (2000 feet)

