CAMSO SKS 796S







HARD SURFACE SOLUTION

A premium solid tire solution for hard-surface operations. Designed with pneumatic comfort in mind, it reduces aperture hole cracking while delivering excellent stability and the best tread life on dry hard-surface operations.

PERFORMAN	H	ì
-----------	---	---

TIRE LIFE

PUNCTURE RESISTANCE

TRACTION



CAMSO SKS 796S



FULL-WIDTH FOOTPRINT

■ Provides excellent stability and tread life

FEA-VALIDATED APERTURE DESIGN


■ Improves ride quality and reduces cracking

REUSABLE WHEEL


Provides lower cost per hour and quicker installation

							3 (3)						
	RIM SIZE				HEEL		LOAD CAPACITY [kg] [lb]						
TIRE SIZE		ACTUAL TIRE DIMENSIONS		Counterbalanced lift trucks			Other states			01.11			
				Load wheel			Steering wheel	Other vehicles		Static			
		O.D. [mm] <i>[in]</i>	0.W. [mm] <i>[in]</i>	0.T.D. [mm] [32nd]	Normal	Quick	15 km/h 9 mph	25 km/h 16 mph	25 km/h 16 mph	6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph
31x10-20 (10-16.5)	7.50	781	237	33			-	4030	3100	4030	3660	3100	4680
		30.7	9.3	42	-	•	-	8885	6835	8900	8100	6850	10350
33x12-20 (12-16.5)	7.50	831	287	40			-	5200	4000	5200	4720	4000	6040
		32.7	11.3	50	-		-	11465	8820	11500	10400	8850	13350
36x14-20 (14-17.5)	7.50	909	326	43			-	6175	4750	6175	5605	4750	7175
		35.8	12.8	54	-	•	-	13650	10500	13650	12350	10500	15850

FEA-ENGINEERED APERTURE DESIGN



WEARABLE TREAD VOLUME COMPARISON



CAMSO SKS 796S TYPICAL SOLID R4

Shows minimized stress around aperture holes for vertical deflection.

Camso SKS 796S offers maximum durability and tread life in extreme hard surface applications.

AUTHORIZED DISTRIBUTOR:

camso.co

